

Service Bulletin

File in Section:

Bulletin No.: 16-NA-102

Date: May, 2016

TECHNICAL

Subject: Duramax Diesel Hard Start, No Start, DTCs P0087, P0088, P0191, P128E or Injection

Pump Replacement

Attention: This Bulletin also applies to any of the models that may be Israel Export vehicles.

Brand:	Model:	Mode	l Year:	VI	N:	Engine:	Transmission:
Biallu.	wiodei.	from	to	from	to		
Chevrolet	Express, Silverado 2500/3500	2010	2016			Diesel (RPOs	
GMC	Savana, Sierra 2500/3500	2010	2016			LML or LGH)	


Condition	A dealer may encounter a customer concern of a hard start or a no start. DTCs P0087, P0088, P0191 or P128E may also be found.
	Normal SI Diagnostics may be inconclusive or lead to Fuel Injection Pump replacement.

Service Procedure

Complete the current SI diagnostics for any symptoms or DTCs found.

If the current SI diagnostic has led to Fuel Injection Pump replacement, Fuel Pressure Regulator 1 must be inspected for magnetic metal debris.

Note: Clean the area around Pressure Regulator 1 before removal. It is possible that road debris could find its way into the regulator port when it is removed. A small piece of dirt on Pressure Regulator 1 does not qualify for the fuel system repairs recommended in this Bulletin.



2698603

Remove the Fuel Injection Pump / Pressure Regulator 1 for inspection.

Page 2 May, 2016 Bulletin No.: 16-NA-102



3541158



354116

If Pressure Regulator 1 has no debris on the screen, complete the SI repair procedure and replace the Fuel Injection Pump.




3541164

If there is a questionable amount of magnetic debris found on Pressure Regulator 1, remove the Fuel Rail Pressure Sensor and/or Fuel Pressure Regulator 2 (Pressure Relief Valve) for inspection.



3541168



3541159

If additional magnetic debris is found on the Fuel Rail Pressure Sensor and/or Fuel Pressure Regulator 2 (Pressure Relief Valve), the Fuel Injection Pump is experiencing the condition described.

Important: If magnetic debris described above is found, complete the repairs listed below:

- Replace all of the parts listed in the Parts Information below.
- Clean and flush all fuel chassis lines, filter pipes, and other engine mounted fuel system pipes that are not being replaced.

- The fuel filter housing must be cleaned with a new fuel filter installed.
- 4. The fuel tank and fuel sender must be cleaned and flushed.

Note: The Indirect Fuel Injector (Hydrocarbon Injector) and its fuel lines must be purged of air any time it is removed or replaced. Failure to do so may damage the injector. Perform the Diesel Particulate Filter (DPF) Regeneration Enable any time the indirect injector or its fuel lines are opened/removed or replaced. This will force regeneration as soon as conditions allow and will purge any air from the system. Refer to *Diesel Particulate Filter (DPF) Regeneration Enable* in SI.

TIP:

After repairs, the following may help with fuel system priming:

- Prime fuel to the fuel filter housing.
- Relieve air by opening the bleed screw at the filter housing.
- Pump the priming ball again until no more air escapes and close the bleed screw.
- Prime until the priming ball is hard.
- There should be at least 10 psi fuel pressure on the fuel system pressure gauge attached to the fuel system service port (schrader valve).
- Crank the engine for up to 15 seconds.
- Key off for one minute.

Repeat the above steps until the engine starts. It is normal for the engine to start and then stall when the fuel system loses prime. Repeated priming will alleviate this concern.

Parts Information

Part			Silverado / Sierra (LML)						Silverado / Sierra (LGH)				Express / Savana (LGH)						
Number	2 ccompact	α.,.	2011	2012	2013	2014	2015	2016	2011	2012	2010	2011	2012	2013	2014	2015	2016		
12664429	FILTER KIT, FUEL	1	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х	Х	Х	Х	Х		
88917036	FILTER, OIL	1	Χ	Х	Х	Х	Χ	Х	Х	Х	Х	Χ	Х	Х	Х	Х	Х		
97363570	GASKET, CTR INT MANIF	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
12635466	GASKET, EGR VLV (LOCR A)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
98062923	GASKET, EGR VLV (LOCR B)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
97223686	GASKET, ENG COOL THERM HSG	2	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
15126137	GASKET-EXH MANIF PIPE	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
97188685	GASKET, EXH TURBO INL PIPE	2	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
97192618	GASKET, EXH TURBO INL PIPE	2	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
12627897	GASKET- TURBO OIL FEED PIPE	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
12637218	GASKET- TURBO OIL RTN PIPE	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
12639312	HOSE ASM- FUEL FEED (RH SIDE OF PUMP, W/ BANJ)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
12639000	HOSE ASM- FUEL RTN	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		

	INJECTOR ASM-	1			.,	l .,			l .,	l	l .,	.,			.,	l .,	
12661071	ASM- INDIRECT FUEL PIPE ASM-	1	X	X	X	Х	X	X	X	X	X	X	X	X	X	Х	Х
12656313	FUEL FEED		Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
94011618	SEAL, COLD START FUEL FEED VLV (O RING)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
12625100	SEAL, COLD START FUEL FEED VLV (O RING)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	х
94036238	SEAL, OIL LVL IND TUBE (O RING)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
94011603	SEAL, THERM BYPASS PIPE (O RING)	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
12670466	PIPE ASM- FUEL HIGH PRESS	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
12641590	SWITCH ASM, ENG FUEL VAC	1	Х		Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
12631851	SEAL-TURBO AIR INL ADAP	1	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
97224993	SENSOR ASM, FUEL TEMP	1	Х						Х		Х	Х	Х	Х	Х	Х	Х
12676436	SENSOR ASM- WAT IN FUEL IND	1											х	х	Х	Х	х
98065521	GASKET-EGR VLV CLR	1	Х	Х	Х	Х	Х	Х	Х	Х							
12644913	BRACKET ASM- FUEL FEED PIPE CLIP	1	Х	Х	Х	Х	Х	Х	Х	х							
12624346	TUBE-FUEL PRESS REG VAC	1	Х	Х	Х	Х	Х	Х	Х	х							
12636270	HOSE-FUEL FEED (ON RH PUMP INLET)	1	Х	Х	Х	Х	Х	Х	Х	х							
12636274	HOSE-FUEL FLTR (ON FILTER OUTLET)	1	Х	Х	Х	Х	Х	Х	х	Х							
12636275	HOSE-FUEL PRESS REG VAC (PIPE TO SERVICE FIT)	1	Х	Х	Х	Х	Х	Х	Х	Х							
12646725	MANIFOLD ASM-F/INJN FUEL FEED	1	Х	х	Х	Х	Х	Х	х	х							
12639779	PIPE ASM- FUEL FEED (FILTER OUT TO PUMP INLET)	1	Х	Х	Х	х	Х	Х	Х	х							
12670460	PIPE ASM- FUEL HIGH PRESS (CYL 2 & 7)	2	Х	Х	Х	Х	Х	Х	Х	Х							
12670468	PIPE ASM- FUEL HIGH PRESS (CYL 1 & 8)	2	Х	Х	Х	Х	Х	Х	Х	Х							
12670469	PIPE ASM- FUEL HIGH PRESS (CYL 3 & 6)	2	Х	Х	Х	Х	Х	Х	Х	х							
12670471	PIPE ASM- FUEL HIGH PRESS (CYL 4 & 5)	2	Х	Х	Х	Х	Х	Х	Х	Х							
12670474	PIPE ASM- FUEL HIGH PRESS (LEFT SIDE OF PUMP)	1	Х	Х	Х	Х	Х	Х	Х	Х							
12670475	PIPE ASM- FUEL HIGH PRESS (RIGHT SIDE OF PUMP)	1	Х	Х	Х	Х	Х	Х	Х	Х							
12629458	SEAL-TURBO AIR INL ADAP	1	Х	Х	Х	Х	Х	Х	Х	Х							
12627913	SEAL-UPR INT MANIF	1	Х	Х	Х	Х	Х	Х	Х	Х							
12645582	HOSE ASM- FUEL RTN (LEFT RAIL TO FEED PIPE)	1		Х	Х	Х	Х	Х		Х							

98065619 GASKET-EGR 1																		
98065520 GASKET-EGR 1	98065519		1	Х	Х	х	Х	Х	Х									
12672028 PUNP KIT-PULE 1	98065523	GASKET- EGR PIPE	1	Х	Х	Х	Х	Х	Х									
12672028 CONTAINS	98065520	GASKET-EGR VLV CLR	1	Х	Х	Х	Х	Х	Х									
12670452	12672028	(CONTAINS FUEL PUMP.	1	х	х	х	х	х	х									
12670427 CONTAINS	98070023	GASKET-EGR VLV CLR	1						Х	Х		Х	Х	Х	Х	Х	Х	Х
12670456 FUEL RTN	12672027	(CONTAINS FUEL PUMP,	1							х	Х	Х	Х	Х	Х	Х	Х	Х
12670457 PIPE ASM- FUEL HIGH PRESS (CYL 6) 1	12636266	HOSE- FUEL RTN	1									Х	Х	Х	Х	Х	Х	Х
12670457 FUEL HIGH PRESS (CVL 6)	12641356	PIPE ASM- FUEL FEED	1									Х	Х	Х	Х	Х	Х	Х
12670463 FUEL HIGH PRESS (CYL 1)	12670457	FUEL HÌGH	1									Х	Х	Х	Х	Х	Х	Х
12670456 FUEL HIGH PRESS (CYL 8)	12670463	FUEL HIGH	1									Х	Х	Х	Х	Х	Х	Х
12670454 FUEL HIGH PRESS	12670456	PIPE ASM- FUEL HIGH PRESS (CYL 8)	1									Х	Х	Х	Х	Х	Х	Х
12670460 PIPE ASM-FUEL HIGH PRESS (CYL 2) 1	12670454	FUEL HÌGH	1									Х	Х	Х	Х	Х	Х	Х
12670464 PIPE ASM-FUEL HIGH PRESS (CYL 3) 1	12670465	PRESS (CYL 1)	1									Х	Х	Х	Х	Х	Х	Х
12670464 FUEL HIGH PRESS (CYL 3) 12670459 FUEL HIGH PRESS (CYL 4 OR 5) 12670453 FUEL HIGH PRES	12670460	PIPE ASM- FUEL HIGH PRESS (CYL 2)	1									Х	Х	Х	Х	Х	Х	Х
12670459 PRESS (CYL 4 OR 5)	12670464	FUEL HIGH	1									Х	Х	Х	Х	Х	Х	Х
12670453 FUEL HIGH PRESS X	12670459	PIPE ASM- FUEL HIGH PRESS (CYL 4 OR 5)	2									Х	Х	Х	Х	Х	Х	Х
SEAL P/S 1 X X X X X X X X X	12670453	FUEL HIGH	1									Х	Х	Х	Х	Х	Х	Х
(O RING) 07369235 GASKET-CTR 1	12639101	PIPE ASM- FUEL RTN	1									Х	Х	Х	Х	Х	Х	Х
	26020642	SEAL, P/S PUMP RSVR (O RING)	1									Х	х	Х	х	Х	Х	Х
	97368325		1									Х	Х	Х	Х	Х	Х	Х

Warranty Information

For vehicles repaired under the Powertrain coverage, use the following labor operation. Reference the Applicable Warranties section of Investigate Vehicle History (IVH) for coverage information.

Labor Operation	Description	Labor Time
		2010-2016 G Van 21.0 Hours*
4080558		2011-2014 C Truck (2WD) 18.0 Hours*
	Diagnose and Clean/Repair Complete Fuel System	2011-2014 K Truck (4WD) 20.0 Hours*
		2015-2016 C and K Truck (2WD and 4WD) 21 Hours*

^{*}This is a unique Labor Operation for bulletin use only. It will not be published in the Labor Time Guide.

Version	3
Modified	April 11, 2016 – Updating the Qty. column of the Parts Information table. April 29, 2016 – Updating the Parts Information table.